

## HV Series Valves

Outstanding performance. Unmatched durability.

### Features

#### Reliability

- Eccentric diaphragm for smooth closing, less water hammer
- Glass-filled polypropylene body for strength
- Reverse flow normally closed design
- Single-filtered pilot flow for maximum reliability
- Trouble-free service with few parts
- Buna-N diaphragm with self-cleaning 90-mesh (200 micron) pilot water filter and stainless steel spring

#### Versatility

- Compact design, 2.54" spin radius for tight installations
- Operates in low-flow and Xerigation® applications when the RBY filter is installed upstream
- Available in multiple fitting types
- External bleed to manually flush system of dirt and debris during installation and system start-up
- Internal bleed for spray-free manual operation
- Unique, easy-to-turn, pressure-assisted flow control mechanism (HVF models only)

#### Ease of Service

- Captive multi-drive screws for easier maintenance
- Your choice of tools to open valve (nut driver, Phillips head screwdriver, slotted head screwdriver)
- Quick access to diaphragm with only four screws
- Diaphragm locating post for reliable service



100-HV


100-HV-MB

100-HV-SS

### Operating Range

- **Pressure:** 15 to 150 psi (1,0 to 10,3 bar)
- **Flow:** 0.2 to 30 gpm (0,05 to 6,82 m<sup>3</sup>/h; 0,01 to 1,89 l/s); for flows below 3 gph (0,68 m<sup>3</sup>/h; 0,19 l/s) or any Xerigation® application, use RBY-100-200MX filter installed upstream
- **Temperature:** water temperature up to 110°F (43°C); ambient temperature up to 125°F (52°C)

### How to Specify



Size  
100: 1" (26/34)

*Note: For non-U.S. applications it is necessary to specify NPT or BSP thread type (1" only)*

## Electrical Specification

- 24 VAC 50/60 HZ Solenoid
- **Maximum Inrush Current:** 0.250 Amps @ 60HZ
- **Holding Current:** 0.143 Amps @ 60HZ
- **Coil Resistance:** 52 to 55 Ohms

## Dimensions

- Height: 4.62" (11,7 cm)
- Height (MB): 4.50" (11,43 cm)
- Length: 4.4" (11,2 cm)
- Length (MB): 5.68" (14,4 cm)
- Width: 3.1" (7,9 cm)

## Models

- 100-HV-NPT
- 100-HV-SS
- 100-HV-MB
- I100-HV-BSP
- I100-HV-BSP-MxM
- 100-HVF-NPT
- 100-HVF-SS
- I100-HVF-BSP

## Specifications

### Electrical Remote Control Valve

The valve shall be normally closed 24 VAC 50/60 Hz solenoid actuated, balanced pressure type capable of a flow rate of 30 GPM (6,82 m<sup>3</sup>/h; 1,89 l/s) with a pressure loss not to exceed \_\_\_\_\_.

The valve pressure rating shall not be less than 150 psi (10,3 bars). The valve body and bonnet shall be constructed of high impact

weather resistant plastic, stainless steel and other chemical/UV resistant materials. The valve shall have a diaphragm constructed of durable Buna-N rubber material with a clog resistant metering orifice. The valve shall have one 90-mesh (200 micron) pilot filter attached to the diaphragm. The valve shall have one fully encapsulated solenoid with captured plunger.

The valve body shall be a 1" globe configuration (26/34) with a \_\_\_\_\_ inlet and \_\_\_\_\_ outlet.

The valve shall be actuated by a low power 0.25 A (6.0 VA) inrush current and 0.15 A (3.6 VA) holding current. The valve shall be capable of on/off control by turning the solenoid 1/4 turn. The valve shall provide a flush mode that is manually activated by 1/2 turn of the bleed screw where external porting is permissible.

The valve shall be of a threaded bonnet design and provide for all internal parts to be removable from the top of the valve without disturbing the valve installation.

The diaphragm shall be a drop-in design which can be installed into the valve body with no special alignment tab.

### Optional Feature Specification

When so indicated on the design, the HVF valve shall have all the specifications of the HV Series remote control valve, plus a unique, easy-to-turn, pressure-assisted flow control mechanism.

The remote control valve shall be manufactured by Rain Bird Corporation, Glendora, California.

### HV and HVF Valve Pressure Loss (psi)

Flow (gpm)	1" HV (psi)	Male x Barb (psi)
1	1.57	1.73
3	2.07	2.03
5	2.38	2.25
10	3.33	2.80
20	4.59	4.45
30	6.14	7.85
40	8.23	13.68

### Valve Pressure Loss (bar) METRIC

Flow (m <sup>3</sup> /h)	Flow (l/s)	1" HV (bar)	Male x Barb (bar)
0,25	0,06	0,11	0,12
0,75	0,21	0,14	0,14
1,00	0,28	0,16	0,16
2,00	0,56	0,23	0,19
5,00	1,39	0,32	0,31
7,50	2,08	0,42	0,54
9,10	2,52	0,57	0,94

**Rain Bird Corporation**  
6991 East Southpoint Road  
Tucson, AZ 85756  
Phone: (520) 741-6100  
Fax: (520) 741-6522

**Rain Bird Technical Services**  
(800) RAINBIRD (1-800-724-6247) (U.S. & Canada)

**Rain Bird Corporation**  
970 West Sierra Madre Avenue  
Azusa, CA 91702  
Phone: (626) 812-3400  
Fax: (626) 812-3411

**Specification Hotline**  
800-458-3005 (U.S. & Canada)

**Rain Bird International, Inc.**  
1000 West Sierra Madre Ave  
Azusa, CA 91702  
Phone: (626) 963-9311  
Fax: (626) 852-7343

The Intelligent Use of Water™  
[www.rainbird.com](http://www.rainbird.com)